

## Technical Datasheet

# POLYESTER FLEECE PSF 60

## Polyester fleece for reinforcing waterproofing layers

### Description – Fields of application

PET crosslapped spunlace non-woven polyester fleece 60 g/m<sup>2</sup>, used to enhance the strength and durability of various waterproofing membranes, such as ISOFLEX, ISOFLEX-PU 500, AQUAMAT-ELASTIC, etc., over the entire surface to be waterproofed or across localized cracks, joints, wall-floor junctions, corners, etc.

### Packaging

1 m x 50 m rolls (50 m<sup>2</sup>), 10 cm x 50 m rolls.

### Storage

Stored in its original, sealed packaging, protected from humidity and UV radiation.

### Technical data

Weight:	60 g/m <sup>2</sup> (min. 54 – max. 66)
Thickness:	0.55 mm
Tensile strength: (EN ISO 13934-2)	
- Machine direction (MD):	160 N
- Cross direction (CD):	150 N
Elongation at break: (EN ISO 13934-2)	
- Machine direction (MD):	30-65%
- Cross direction (CD):	35-80%

**ISOMAT S.A.**  
BUILDING CHEMICALS, MORTARS & PAINTS  
HEADQUARTERS – THESSALONIKI, GREECE  
17<sup>th</sup> km Thessaloniki – Ag. Athanasios Road  
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece  
T +30 2310 576000  
[www.isomat.eu](http://www.isomat.eu) e-mail: [support@isomat.eu](mailto:support@isomat.eu)